



TL-WR840N

Velocidad N inalámbrica de 300Mbps

WIRELESS

Standards	Wi-Fi 4 IEEE 802.11n/b/g 2.4 GHz
WiFi Speeds	N300 2.4 GHz: 300 Mbps (802.11n)
WiFi Range	2 Bedroom Houses 2× Fixed Antennas
WiFi Capacity	Legacy
Working Modes	Router Mode Access Point Mode Range Extender Mode

WIRELESS	
WISP Mode	
HARDWARE	
Processor	Single-Core CPU
Ethernet Ports	1× 10/100 Mbps WAN Port 4× 10/100 Mbps LAN Ports
Botones	Reset Button
Power	9 V = 0.6 A
SEGURIDAD	
WiFi Encryption	WEP WPA WPA2 WPA/WPA2-Enterprise (802.1x)
Network Security	SPI Firewall Access Control IP & MAC Binding Application Layer Gateway
Guest Network	1× 2.4 GHz Guest Network
SOFTWARE	
Protocols	IPv4 IPv6
Parental Controls	URL Filtering Time Controls
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP
Quality of Service	QoS by Device
NAT Forwarding	Port Forwarding Port Triggering DMZ UPnP
IPTV	IGMP Proxy

SOFTWARE	
	IGMP Snooping
DHCP	Address Reservation DHCP Client List Server
DDNS	NO-IP Comex DynDNS
Management	Tether App Webpage Check Web Emulator>
PHYSICAL	
Dimensions (W×D×H)	7.2 × 5.0 × 1.4 in (182 × 128 × 35 mm)
Package Contents	Wi-Fi Router TL-WR840N Power Adapter RJ45 Ethernet Cable Quick Installation Guide
OTHER	
System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser Cable or DSL Modem (if needed) Subscription with an internet service provider (for internet access)
Certifications	FCC, CE, RoHS
Environment	Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
TEST DATA	
WiFi Transmission Power	CE: <20dBm(2.4GHz) FCC: <30dBm

TEST DATA

WiFi Reception Sensitivity

270M: -68dBm@10% PER
 130M: -68dBm@10% PER
 108M: -68dBm@10% PER
 54M: -68dBm@10% PER
 11M: -85dBm@8% PER
 6M: -88dBm@10% PER
 1M: -90dBm@8% PER

*Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage are not guaranteed and will vary as a result of 1) environmental factors, including building materials, physical objects, and obstacles, 2) network conditions, including local interference, volume and density of traffic, product location, network complexity, and network overhead, and 3) client limitations, including rated performance, location, connection, quality, and client condition.

Subscription

Dirección de correo

[Regístrate](#)

Síguenos

Acerca de Nosotros

[Perfil Corporativo](#)

[Contáctanos](#)

[Privacy Policy](#)

Prensa

[Noticias](#)

[Premios](#)

[Próxima Exhibición](#)

Dónde Comprar

[Almacenes de Cadena](#)

[Tiendas en línea](#)

[Distribuidores](#)

[Puntos de Venta](#)

[Canales Especializados en SMB](#)

Learning Center

[Technology Library](#)

Colombia / Español

Copyright © TP-Link Corporation Limited. 2021. Todos los derechos reservados